



WIA BlueFX

Part No: 235660

PROTECTION, COMFORT & PERFORMANCE AT AN AFFORDABLE PRICE.

NEW RELEASE

SUITS STICK, MIG, TIG & PLASMA CUTTING

HIGH IMPACT RATING

2 ARC SENSORS



AUSTRALIAN STANDARDS




AUSTRALIAN STANDARDS

Tested in Australia, the lens and helmet comply with Australian Standards AS/NZS 1338.1 (Auto-Darkening) and AS/NZS 1337.1 B (High Impact).

OPERATOR COMFORT

High quality headgear - comfortable, lightweight and fully adjustable for easy adjustment to provide maximum face and neck protection. Weighs only 510.3g.



VARIABLE SHADE CONTROL

Variable control for adjustment of shade, lens sensitivity and delay for maximum control when welding. Shade 9-13.



MAGNIFYING LENS HOLDER


Built-in provision for magnifying lens*, if required. *Magnifying lens not included.





WIA BlueFX

Part No: 235660



BATTERY POWERED WITH SOLAR-ASSIST

The replaceable battery life is extended by inbuilt UV solar cells which absorb power from the arc while welding. Delivers up to 1500 hours of interruption free welding with MIG, Stick, TIG and Plasma power sources – meaning your helmet will always be ready when you are.




GRIND MODE

Comes standard with Grind Mode, meaning you can use one helmet for all your welding requirements - including weld preparation and clean-up.

LENS DELAY CONTROL

Used to adjust the time for the lens to switch to clear state after welding. Useful in eliminating bright rays present in high amp applications. Adjusts from 0.1 second-min to 1.0 second-max.



DUAL ARC SENSORS

Provides continuous arc sensing capability. Lens automatically switches from light state 4 to adjustable welding shades 9-13 when an arc is struck. Lens darkening reaction time 1/12,000 sec.



1 YEAR WARRANTY

Like all WIA products, this product is manufactured with quality in mind. Tested under stringent conditions, we provide a 1 year warranty for your peace of mind.

SENSITIVITY CONTROL

Sensitivity control makes the lens more responsive to different light levels in various welding processes. Use mid-range or 30-50% sensitivity setting for most applications.

PRODUCT SPECIFICATIONS

Part Number	235660
Applications	Stick, MIG, TIG & Plasma Cutting
Viewing Area	97 X 46mm
Cartridge Size	110 X 90mm
Variable Shades	9 to 13
Light State	4
Grind Mode	Yes
Switching Speed (Light to Dark)	1/12,000 Sec
Delay Speed (Dark to Light)	0.1 - 1.0 Sec
Arc Sensors	2
Weight	510.3g
Power	Lithium Battery & Solar-Assist
On/Off Control	Automatic
Operating Temperature	-5 °C to +55 °C
Warranty	1 Year (Auto-Darkening Lens Only)

STANDARDS

AS/NZS 1338.1 (Auto-Darkening)
AS/NZS 1337.1 B (High Impact)

PARTS AND ACCESSORIES

Outside Lens Cover (pkt 5)	235665P
Inside Cover Lens (pkt 5)	770237P
Ratchet Headgear Assembly	770246
Replaceable Battery	217043
Auto-Darkening Lens	235662
Kit Lens Holder	235661
Gasket Cover Lens	235664
Magnifying Lens 1.5x	212238P
Magnifying Lens 2.0x	212240P
Magnifying Lens 2.5x	212242P

