



# Weldmatic 250i

Part No: CP138-1



**✓ GASLESS**    **✓ ALUMINIUM MIG**    **✓ MILD STEEL**

## VERSATILE, PORTABLE, MULTI-PROCESS INVERTER WITH VRD

- > Single phase, multi-process inverter capable of handling MIG, Stick and Lift-TIG processes.
- > With 250A of MIG, the Weldmatic 250i suits a wide range of applications - from fencing jobs to construction sites.

### PACKAGE INCLUDES

- Euro Gun Cable (3.6m)
- Work Lead (3m)
- Industrial Twist Lock Electrode Holder (3m)
- Gas Regulator
- Drive Rollers - 0.9/1.2mm 'V' Groove, 0.9/1.2mm Knurled (Gasless)
- Tips (0.6/0.8/0.9/1.2mm)

### VRD

Built in VRD delivers added safety when operating in Stick or Lift-TIG mode and meets the requirements of site work. Fully compliant to Australian Standards AS 60974.1 & AS1674.2 CAT C.

### PORTABLE

At 25.5kg, the Weldmatic 250i is portable and comes supplied with 2 handles for easy two person lift, making it suitable for onsite maintenance.

### QUICK & EASY GUN CABLE ASSEMBLY

Supplied with a tradesman quality gun and cable complete with euro connector for easy fitting and removal.

### BUILT-IN OPERATOR SAFETY

The power source features a built-in thermal protection device that will activate if the machine is operated beyond its safe thermal operating zone.

### GAS OR GASLESS

Suits gas shielded and gasless flux cored wires.

### SPOOL CAPACITY

Suits 5kg & 15kg spool.

### EASY SET-UP & ADJUSTMENT

The control panel allows easy selection for gas and wire type, with infinitely variable voltage and wire speed, indicated on the digital display.

### TROLLEY WITH DRAWER [OPTIONAL]

P/N AM358.

### WARRANTY\*

With a 2 year unlimited warranty, covering parts and labour, and supported by an Australia wide service network, you can be guaranteed you're buying reliability and performance.

\*Power source only.



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	RECOMMENDED GENERATOR kVA	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	WIRE SIZE RANGE (MM)	SHIPPING WEIGHT	MACHINE WEIGHT
240 Vac - 50/60 Hz	20.2 Amps	45 Amps	13 kVA	15 Amps*	250 A, 26.5 V, 20% Duty Cycle 112 A, 19.6 V, 100% Duty Cycle	30 - 250 Amps	0.6 - 0.9 solid 0.8 - 1.2 cored 1.0 aluminium	36kg	25.5kg

\*15 Amp plug for commissioning purposes only